

# MATERIAL SAFETY DATA SHEET

## ETHANE

(Please ensure that this MSDS is received by an appropriate person)

Date: June 2017

Version1

Ref no.: MSNIG013

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT IDENTIFICATION

Product Name ETHANE  
Chemical Formula C<sub>2</sub>H<sub>6</sub>  
Trade Name Ethane  
Colour coding Signal Red (A.11) body with the relevant stenciling on the body.  
Valve female Neriki – Brass 5/8-inch BSP left hand  
Company Identification BOC Gases Nigeria Plc  
Block H Plot 1-3 Apapa Oshodi Expressway  
Oshodi, Lagos, Nigeria  
Tel No: +234 (01) 3429178

**EMERGENCY No** +234(0)8076411479(24 hours)

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name Ethane  
Chemical Family Saturated hydrocarbon  
CAS No. 74-84-0  
UN No. 1035  
ERG No 115  
Hazchem Warning 2 A Flammable gas

### 3 HAZARDS IDENTIFICATION

**Main Hazards** All cylinders are portable gas containers, and must be regarded as pressure vessels at all times. Ethane is highly flammable and is slightly heavier than air. This could cause pockets of gas to collect in low-lying areas.

**Adverse Health Effects** The gas is a simple asphyxiant, and at high concentrations could cause narcosis. No definite symptoms have been observed in concentrations up to 5%. Direct contact with the liquid form can cause frostbite and freeze-burns in exposed tissues.

**Chemical hazards** None.

#### Biological Hazards

Eye contact	(gas)	No known effect
	(Liquid)	Serious burns
Skin contact	(gas)	No known effect
	(Liquid)	Serious burns
Ingestion	(liquid)	Serious burns

### 4 FIRST AID MEASURES

Prompt medical attention is mandatory in all cases of overexposure to vaporized Ethane. Rescue personnel should be equipped with self-contained breathing apparatus. In case of frostbite from contact with the liquid phase, place the frostbitten part in warm water, about 40 - 42°C. If warm water is not available, or is impractical to use, wrap the affected part gently in blankets. Encourage the patient to exercise the affected part whilst it is being warmed. Do not remove clothing while frosted. Conscious persons should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be removed to an uncontaminated area, and given mouth-to-mouth resuscitation and supplemental oxygen.

#### Eye contact

**(With liquid phase)** Immediately flush with large quantities of tepid water, or with sterile saline solution. Seek medical attention.

#### Skin contact

**(With liquid phase)** See above for handling frostbite.

**Ingestion** Ingestion is unlikely. Liquid could cause severe burns.

### 5 FIRE FIGHTING MEASURES

**Extinguishing media** Do not extinguish fire unless the leakage can be stopped. Do not use water jet, use dry chemical, CO<sub>2</sub> or foam.

**Specific hazards** The rupturing of cylinders or bulk containers due to excessive exposure to a fire could result in a BLEVE (Boiling Liquid Expanding Vapour Explosion), with disastrous effects. As the flammability limits in air for Ethane are between 3 and 12.5%, extreme care must be taken when handling leaks.

**Emergency actions** If possible, shut off the source of the spillage. Evacuate area. Post notices, "No naked lights - no smoking". Prevent liquid or vapour from entering sewers, basements and workpits. Keep cylinders or bulk vessels cool by spraying with water if exposed to a fire. CONTACT THE NEAREST BOC BRANCH

**Protective clothing** Self-contained breathing apparatus. Safety gloves and shoes, or boots, should be worn when handling cylinders.

**Environmental Precautions** Vaporized Ethane gas is heavier than air and could form pockets of oxygen-deficient atmosphere in low-lying areas.

### 6 ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Do not enter any area where Ethane has been spilled unless tests have shown that it is safe to do so.

**Environmental Precautions** the danger of widespread formation of explosive Ethane/air mixtures should be taken into account. Accidental ignition could result in a massive explosion.

**Small spills** Do not extinguish the fire unless the leakage can be stopped immediately. Once the fire has been extinguished and all spills have been stopped, ventilate the area.

**Large spills** Stop the source if it can be done without risk. Contain the leaking liquid, with sand or earth, or disperse with special water/fog spray nozzle. Allow evaporating. Take the precautions as listed above under "Emergency Actions". Restrict access to the area until completion of the clean-up procedure. Ventilate the area using forced draught if necessary. All electrical equipment should be flameproof.

### 7 HANDLING AND STORAGE

Cylinders containing Ethane should only be handled and stored in the vertical position. Cylinders should never be rolled. Do not allow cylinders to slide or come into contact with sharp edges and they should be handled carefully. Ensure that cylinders are stored away from other oxidants. Comply with all local legislation. Keep out of reach of children.

## MATERIAL SAFETY DATASHEET ETHANE

(Please ensure that this MSDS is received by an appropriate person)

Date: June 2017

Version1

Ref no.: MSNIG013

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Occupational</b>	as vaporized Ethane is a simple asphyxiant,
<b>Exposure hazards</b>	avoid any areas where spillage has taken place. Only enter once testing has proved the atmosphere to be safe.
<b>Engineering</b>	Engineering control measures are preferred to
<b>Control measures</b>	reduce exposures. General methods include forced-draught ventilation, separate from other exhaust ventilation systems. Ensure that sufficient fresh air enters at, or near, floor level. Ensure that all electrical equipment is flameproof.
<b>Personal protection</b>	Self-contained breathing apparatus should always be worn when entering an area where oxygen depletion may have occurred. Safety goggles, gloves and shoes or boots should be worn when handling cylinders.
<b>Skin</b>	Wear loose-fitting overalls, preferably without pockets.

## MATERIAL SAFETY DATASHEET

### ETHANE

(Please ensure that this MSDS is received by an appropriate person)

Date: June 2017

Version1

Ref no.: MSNIG013

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

##### PHYSICAL DATA

Chemical Symbol	C <sub>2</sub> H <sub>6</sub>
Molecular Weight	30,07
Specific volume @ 20°C & 101,325 kPa	796 ml/g
Relative density of gas @ 101,325 kPa (Air=1)	1,048
Auto ignition temperature	472,2°C
Flammability limits in air	3,0 - 12,5% (by volume)
Colour	None
Taste	None
Odour	None

#### 10 STABILITY AND REACTIVITY

**Conditions to avoid** The dilution of the oxygen concentration in the atmosphere to levels that cannot support life. The formation of explosive gas/air mixtures.

**Incompatible Materials** Any common, commercially available metals may be used with Ethane because it is non-corrosive, though installation must be designed to withstand the pressures involved and must comply with all state and local regulations.

**Hazardous Decomposition Products** Ethane is relatively stable. However, on combustion, toxic compositions, typically carbon monoxide may be formed, depending on conditions.

#### 11 TOXICOLOGICAL INFORMATION

Acute Toxicity	No known effect
Skin & eye contact	No known effect
Chronic Toxicity	No known effect
Carcinogenicity	Severe cold burns can result in carcinoma
Mutagenicity	No known effect
Reproductive Hazards	No known effect

For further information, see Section 3. Adverse Health Effects

#### 12 ECOLOGICAL INFORMATION

Vaporized Ethane is heavier than air, and can cause pockets of oxygen-depleted atmosphere in low-lying areas. It does not pose a hazard to the ecology, unless the gas/air mixture is ignited.

#### 13 DISPOSAL CONSIDERATIONS

**Disposal Methods** Disposal of Ethane, as with other gases, should be undertaken only by personnel familiar with the gas and the procedures for disposal. Contact the supplier for instructions. In general, should it become necessary to dispose of Ethane, the best procedure, as for other flammable gases, is to burn them in suitable burning units available in the plant. This should be done in accordance with appropriate regulations.

**Disposal of Packaging** The disposal of containers must only be handled by the gas supplier.

#### 14 TRANSPORT INFORMATION

##### ROAD TRANSPORTATION

UN No.	1035
ERG No	115
Hazchem warning	2 A Flammable gas

##### SEA TRANSPORTATION

IMDG	1035
Label	Flammable gas

##### AIR TRANSPORTATION

ICAO/IATA Code	1035
Class	2.1
Packaging group	none
Packaging instructions	
- Cargo	200
- Passenger	Forbidden
Maximum quantity allowed	
- Cargo	150 kg
- Passenger	Forbidden

#### 15 REGULATORY INFORMATION

Reference standard: SANS 10234 and supplement  
National legislation: OHSAct and Regulation (85 of 1993)

#### 16 OTHER INFORMATION

Bibliography  
SANS 10234-Global Harmonized System of Classification and Labelling Chemicals and Matheson Gas Data Book

#### EXCLUSION OF LIABILITY

Information contained in this publication is accurate at the date of publication. The company does not accept liability arising from the use of this information, or the use, application, adaptation or process of any product described herein.