

MATERIAL SAFETY DATASHEET HELIUM

(Please ensure that this MSDS is received by an appropriate person)

Date: June 2017 Version1

Ref no.: MSNIG016

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION Product Name Helium Chemical Formula He

Trade Names Helium, Technical (N2.7)

> Helium, High Purity (N4.5) Helium, Instrument, Grade (N4.5)

Helium, UHP (5.0) Helium, Research (N6.0)

Colour Coding Mid Brown (B.07) body with the

appropriate grade decal affixed centrally to the body of the cylinder (N.B. Research grade Helium does not

have a decal on the cylinder)

All grades have the Neriki - Brass 5/8 Valves

inch BSP right hand, positive pressure

valves fitted.

BOC Gases Nigeria Plc Company Identification

Block H Plot 1-3 Apapa Oshodi

Expressway

Oshodi, Lagos, Nigeria Tel No: +234 (01) 3429178

+234(0)8076411479 (24 hours) EMERGENCY No.

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name Helium Chemical Family Inert Rare Gas CAS No. 7440-59-7 UN No 1046 ERG No. 121

Hazchem Warning 2 C Non flammable gas

HAZARDS IDENTIFICATION

Main Hazards. Helium does not support life. It can act as a simple asphyxiant by diluting the concentration of oxygen in air below the levels necessary to support life.

Adverse Health Effects. Helium is non-toxic and inert. Inhalation in excessive concentrations can result in dizziness, nausea, vomiting, loss of consciousness, and death. Death may result from errors in judgement, confusion or loss of consciousness which prevents selfrescue. At low oxygen concentrations, unconsciousness and death may occur in seconds without warning.

Chemical Hazards. Helium is extremely inert and forms no known chemical compounds.

Biological Hazards. Helium is extremely light and disperses very rapidly into the atmosphere. No known hazard.

Vapour Inhalation. As Helium acts as a simple asphyxiant death may result from errors in judgement, confusion, or loss of consciousness which prevents self-rescue. At low oxygen concentrations, unconsciousness and death may occur in seconds without warning.

Eye Contact No known effects. **Skin Contact** No known effects.

Ingestion (See "Vapour Inhalation" above).

FIRST AID MEASURES

Prompt medical attention is mandatory in all cases of overexposure to Helium. Rescue personnel should be equipped with self-contained breathing apparatus. Conscious persons should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be removed to an uncontaminated area, and given mouth-to-mouth

resuscitation and supplemental oxygen. **Eve Contact** No known effect. **Skin Contact** No known effect. Ingestion (See section above).

FIRE FIGHTING MEASURES

Extinguishing media As Helium disperses rapidly into the

atmosphere, it would have little effect on the fire. The appropriate extinguishant should be used for the type of combustible material

involved.

Specific Hazards Helium does not support life. It can act as a

asphyxiant by diluting concentration of oxygen in the air below the

levels to support life.

Emergency Actions If possible, shut off the source of excess

> helium. Evacuate area. All cylinders should be removed from the vicinity of the fire. Cylinders that cannot be removed should be cooled with water from a safe distance. CONTACT THE NEAREST

BRANCH.

Protective Clothing Self contained breathing apparatus. Safety

gloves and shoes, or boots, should be worn

when handling cylinders.

Environmental precautions. As the gas is lighter than air, ensure

that it is not trapped in confined spaces, otherwise this could lead to the formation of an oxygen- deficient atmosphere. Ventilate all confined spaces using forced draught if

necessary.

ACCIDENTAL RELEASE MEASURES

Personal Precautions Do not enter any area where Helium has been

spilled unless tests have shown that it is safe

to do so.

Environmental Helium does not pose a hazard to the

precautions environment.

Small spills Shut off the source of escaping Helium.

Ventilate the area.

Large spills Shut off the source of the spill if this can be

done without risk. Restrict access to the area

completion of the clean-up procedure.

HANDLING AND STORAGE

Do not allow cylinders to slide or come into contact with sharp edges. Helium cylinders may be stacked horizontally provided that they are firmly secured at each end to prevent rolling. Use a "first in - first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Keep out of reach of children.



MATERIAL SAFETY DATA SHEET HELIUM

(Please ensure that this MSDS is received by an appropriate person)

Date: June 2017 Version1

Ref no.: MSNIG016

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Hazards. As Helium is a simple asphyxiant avoid any areas where spillage has taken place. Only enter once testing has proved the

atmosphere to be safe.

Engineering Control measures. Engineering control measures are

preferred to reduce the leakage of Helium into

the atmosphere.

Personal protection Self-contained breathing apparatus should

always be worn when entering area where oxygen depletion may have occurred. Safety goggles, gloves and shoes or boots should be

worn when handling cylinders.

Skin No known effect.

9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL DATA

 $\begin{array}{lll} \text{Chemical Symbol} & \text{He} \\ \text{Molecular Weight} & 4,003 \\ \text{Density of Gas 1atm and 21.1 °C} & 0.166 \text{kg/m}^3 \\ \text{Relative density (Air = 1) @ 101,325 kPa} & 0,138 \\ \text{Colour} & \text{None} \\ \text{Taste} & \text{None} \\ \text{Odour} & \text{None} \end{array}$

10 STABILITY AND REACTIVITY

Conditions to avoid Never use cylinders as rollers or supports, or

for any other purpose than the storage of Helium. Never expose the cylinder to excessive heat, as this may cause sufficient build-up of pressure to rupture the cylinders.

Incompatible Materials. As Helium is inert it may be contained in systems constructed of any of the common

systems constructed of any of the common metals which have been designed to safely withstand the pressures involved.

Hazardous Decomposition Products. None11

11 TOXICOLOGICAL INFORMATION

Acute Toxicity

Skin & eye contact

Chronic Toxicity

Carcinogenicity

Mutagenicity

Reproductive Hazards

No known effect.

(For further information see Section 3. Adverse Health Effects).

12 ECOLOGICAL INFORMATION

Helium does not pose a hazard to the ecology.

13 DISPOSAL CONSIDERATIONS

Disposal Methods Small amounts may be blown to the

atmosphere under controlled conditions. Large amounts should only be handled by the

gas supplier.

Disposal of packaging The disposal of cylinders must only be

handled by the gas supplier.

14 TRANSPORT INFORMATION

ROAD TRANSPORTATION

UN No. 1046 ERG No. 121

Hazchem warning 2C Non-flammable gas

SEA TRANSPORTATION

IMDG 1046

Class

Packaging group Label

Label Non-flammable gas AIR TRANSPORTATION

ICAO/IATA Code 1046 Class 2.2

Class Packaging group

Packaging instructions

- Cargo 200 - Passenger 200

Maximum quantity allowed

Cargo 150kg Passenger 75kg

15 REGULATORY INFORMATION

Reference standard: SANS 10234 and supplement National legislation: OHSAct and Regulation (85 of 1993)

16 OTHER INFORMATION

SANS 10234-Globally Harmonized System of Classification and Labelling of Chemicals and Matheson Gas data book

EXCLUSION OF LIABILITY

Information contained in this publication is accurate at the date of publication. The company does not accept liability arising from the use of this information, or the use, application, adaptation or process of any products described



MATERIAL SAFETY DATA SHEET HELIUM

(Please ensure that this MSDS is received by an appropriate person)

Date: June 2017 Version1

Ref no.: MSNIG016